

PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	350mm • 13.8"
Width	140 mm • 5.5"
Height	170 mm • 6.7"
Weight	4 Kgs • 8.8 lbs
FEEDING	
Pressure range	5.5 - 7 bar / 78-99 psi
Air consumption	12 L/s - 25 cuft/min
PERFORMANCE	
Max. tension force	3000N - 4500N -6.5bar-92psi
Tensioning speed	5mt/m 4500N - 7mt/m 3000N
Sealing	Seal single notch
Joint strength	80% of breaking strength*
Gear ratio	-

* variable according to strap type

MODEL			
CODE	TYPE	STRAP	THICKNESS
T401321	ITA40 - 13mm-1/2"-3000N	R 850N/mm ²	0.016" - 0.031"
		R 1100N/mm ²	0.016" - 0.025"
T401621	ITA40 - 16mm-5/8"-3000N	R 850N/mm ²	0.016" - 0.031"
		R 1100N/mm ²	0.016" - 0.025"
T401921	ITA40 - 19mm-3/4"-3000N	R 850N/mm ²	0.016" - 0.031"
		R 1100N/mm ²	0.016" - 0.025"
T401331	ITA40 - 13mm-1/2"-4500N	R 850N/mm ²	0.016" - 0.031"
		R 1100N/mm ²	0.016" - 0.025"
T401631	ITA40 - 16mm-5/8"-4500N	R 850N/mm ²	0.016" - 0.031"
		R 1100N/mm ²	0.016" - 0.025"
T401931	ITA40 - 19mm-3/4"-4500N	R 850N/mm ²	0.016" - 0.031"
		R 1100N/mm ²	0.016" - 0.025"

SEAL SINGLE NOTCH

