

S-555 Semi-Automatic Strapping Machine



Front and rear hinged tables open completely



Outside tensioning adjustment with indicator



Reliable tensioning system



Adjustable table height



Strong castors with brake

Features

1. Reliable and Up-To-Date Features

- * Reliable tensioning system: main roller is DC motor-driven
- * Wide range of tensioning: 2 - 50kg
- * Smart cutting system: available for various strapping thicknesses without any adjustments
- * Economical and versatile: capable of running 5 - 15.5mm wide and 0.4 - 0.7mm thick strapping

2. Easy Maintenance

- * Fewer mechanical parts
- * PCB: easy plug and play troubleshooting and parts replacement system
- * Front and rear hinged tables open completely for easy access
- * Easily accessible track guide and main roller

3. Physical Ergonomics

- * Outside tensioning adjustment with indicator
- * Adjustable table height: 750 - 830mm

Specification

Machine Size	L 845 x W 430 x H 750mm
Table Height	750 ~830mm (adjustable)
Cycle Time	2 sec. /strap
Min. Package Size	W 45 x H 25mm
Strap Width	5, 6, 9, 12, 15.5mm (adjustable)
Strap Thickness	0.4~ 0.7 mm
Tension Range	2~50 Kgs
Reel Inside Diameter	200, 230, 280mm (specified)
Power Consumption	0.5 7 KW
Power Supply	100/110/220/230/240V, 50/60Hz, 1PH
M/C Weight	65Kgs

Specification subject to change without notice.



P (03) 9770-1728
F (03) 9770-1851
E info@liveindustrial.com.au
W www.liveindustrial.com.au
M PO Box 5137, Frankston South VIC 3199